

Energy Management

1 Source LED TL Series Lighting

CALL SMPW OR YOUR
LOCAL SALES REP FOR
MORE INFORMATION
OR A QUOTE TODAY!
TOLL FREE:
800-767-9855

TL Series: Universal Voltage LED for Ceilings


The TL Series LED Lighting Fixtures from 1 Source LED are a multiple solution, energy efficient option to replace T8 and T12 fluorescent lighting. The Universal 100-277 Volt LED Fixture is a simple retrofit to existing fluorescent ceiling lighting in supermarket, convenience stores, hotels, hospitals, schools, and offices. By simply bypassing the existing Fluorescent Ballast, the TL Series LED Lamp can be retrofit to any application currently using inefficient Fluorescent Lighting!

Product Specifications

- UL Listed & in Accordance with ETL, NSF, & FCC
- Universal Line Voltage Model Operates at 100-277VAC with Internal Driver
- 4' LED Tube Light Voltage 100-277VAC Model Operates at 15 Watts / 1590 Lumens
- Up to 60% Energy Savings Based on Lighting Efficiency & Heat Reduction
- Up to 84 CRI & 110 Lumens Per Watt!
- Quiet Operation / **No Flicker**
- No UV or RF Interference
- Can Withstand Higher Levels of Shock & Vibration
- 50,000 Hour Lifetime Rating
- 5 Year Warranty
- LM79 & LM80 Certification
- Medium Bi-Pin, Single Pin & High Output Lamp Ends Available
- Rotating Field Adjustable Lamp End Option or Configuration (Custom Order)
- 3500K - 6100K Color Temperature Standard
- Rebate Eligible



G13 BiPin

Rotating
G13 BiPinFa8
Lamp EndR17d
Lamp End

Stock No.	Description	Color Temp.	Weight
TL2-UNV-35K	2' LED Lamp, Clear Lens, 120-277VAC, 9W, 954 Avg. Lumens	3500K	1.5 Lbs.
TL2-UNV-35KFR	2' LED Lamp, Frosted Lens, 120-277VAC, 9W, 756 Avg. Lumens	3500K	1.5 Lbs.
TL2-UNV-41K	2' LED Lamp, Clear Lens, 120-277VAC, 9W, 954 Avg. Lumens	4100K	1.5 Lbs.
TL2-UNV-41KFR	2' LED Lamp, Frosted Lens, 120-277VAC, 9W, 756 Avg. Lumens	4100K	1.5 Lbs.
TL2-UNV-61K	2' LED Lamp, Clear Lens, 120-277VAC, 9W, 954 Avg. Lumens	6100K	1.5 Lbs.
TL2-UNV-61KFR	2' LED Lamp, Frosted Lens, 120-277VAC, 9W, 756 Avg. Lumens	6100K	1.5 Lbs.
TL3-UNV-35K	3' LED Lamp, Clear Lens, 120-277VAC, 13W, 1272 Avg. Lumens	3500K	2.0 Lbs.
TL3-UNV-35KR	3' LED Lamp, Frosted Lens, 120-277VAC, 13W, 1008 Avg. Lumens	3500K	2.0 Lbs.
TL3-UNV-41K	3' LED Lamp, Clear Lens, 120-277VAC, 13W, 1272 Avg. Lumens	4100K	2.0 Lbs.
TL3-UNV-41KFR	3' LED Lamp, Frosted Lens, 120-277VAC, 13W, 1008 Avg. Lumens	4100K	2.0 Lbs.
TL3-UNV-61K	3' LED Lamp, Clear Lens, 120-277VAC, 13W, 1272 Avg. Lumens	6100K	2.0 Lbs.
TL3-UNV-61KFR	3' LED Lamp, Frosted Lens, 120-277VAC, 13W, 1008 Avg. Lumens	6100K	2.0 Lbs.
TL4-UNV-35K	4' LED Lamp, Clear Lens, 120-277VAC, 15W, 1590 Avg. Lumens	3500K	2.3 Lbs.
TL4-UNV-35KFR	4' LED Lamp, Frosted Lens, 120-277VAC, 15W, 1260 Avg. Lumens	3500K	2.3 Lbs.
TL4-UNV-41K	4' LED Lamp, Clear Lens, 120-277VAC, 15W, 1590 Avg. Lumens	4100K	2.3 Lbs.
TL4-UNV-41KFR	4' LED Lamp, Frosted Lens, 120-277VAC, 15W, 1260 Avg. Lumens	4100K	2.3 Lbs.
TL4-UNV-61K	4' LED Lamp, Clear Lens, 120-277VAC, 15W, 1590 Avg. Lumens	6100K	2.3 Lbs.
TL4-UNV-61KFR	4' LED Lamp, Frosted Lens, 120-277VAC, 15W, 1260 Avg. Lumens	6100K	2.3 Lbs.
TL5-UNV-41K	5' LED Lamp, Clear Lens, 120-277VAC, 19W, 2014 Avg. Lumens	4100K	2.5 Lbs.
TL6-UNV-41K	6' LED Lamp, Clear Lens, 120-277VAC, 23W, 2438 Avg. Lumens	4100K	2.5 Lbs.
TL8-UNV-41K	8' LED Lamp, Clear Lens, 120-277VAC, 30W, 2520 Avg. Lumens	4100K	3.5 Lbs.

**COMBINE WITH SMPW
SHELVING FOR A GREAT
LOOKING PRODUCT
PRODUCING MAXIMUM
EFFICIENCY!**

Energy Management

1 Source LED TL Series Lighting


TL Series: 36VDC LED for Display Cases

The 36 Volt LED Fixture is UL Listed and approved for installation in wet locations, which makes these the perfect LED for shelf and canopy installation in refrigerated display cases. These low voltage LED fixtures are capable of installing directly to the existing T8 or T12 lamp holders and with an external driver pre-wired to the light kit, just bypass the fluorescent ballast and install the shelf for a true “plug & play” LED shelf lighting option.



Product Specifications & Features

- UL Listed
- Mounts on Existing T8 or T12 Lampholders
- True “Plug & Play” LED Shelf Light
- Simple on-site Installation: Bypass the existing ballasts & Plug in the Light Kit.
- Low Voltage 24VDC Model Operates at 36VDC with External Constant Current Driver
- 4’ LED Tube Light Low Voltage 36VDC Model Operates at 20 Watts / 2200 Lumens
- Up to 60% Energy Savings Based on Lighting Efficiency & Heat Reduction
- Up to 84 CRI & 110 Lumens Per Watt
- Quiet Operation / **No Flicker**
- 50,000 Hour Lifetime Rating
- 5 Year Warranty
- LM79 & LM80 Certification
- Medium Bi-Pin, Single Pin & High Output Lamp Ends Available
- Approved for use in Wet Locations
- 2700K - 6100K



Stock No.	Description	Color Temp.	Weight
TL2-36V-30K	2' LED Lamp, 36VDC, For Canopy/Shelf	3000K	1.5 Lbs.
TL2-36V-35K	2' LED Lamp, 36VDC, For Canopy/Shelf	3500K	1.5 Lbs.
TL2-36V-41K	2' LED Lamp, 36VDC, For Canopy/Shelf	4100K	1.5 Lbs.
TL3-36V-30K	3' LED Lamp, 36VDC, For Canopy/Shelf	3000K	1.8 Lbs.
TL3-36V-35K	3' LED Lamp, 36VDC, For Canopy/Shelf	3500K	1.8 Lbs.
TL3-36V-41K	3' LED Lamp, 36VDC, For Canopy/Shelf	4100K	1.8 Lbs.
TL4-36V-30K	4' LED Lamp, 36VDC, For Canopy/Shelf	3000K	2.0 Lbs.
TL4-36V-35K	4' LED Lamp, 36VDC, For Canopy/Shelf	3500K	2.0 Lbs.
TL4-36V-41K	4' LED Lamp, 36VDC, For Canopy/Shelf	4100K	2.0 Lbs.
TL5-36V-30K	5' LED Lamp, 36VDC, For Canopy/Shelf	3000K	2.2 Lbs.
TL5-36V-35K	5' LED Lamp, 36VDC, For Canopy/Shelf	3500K	2.2 Lbs.
TL5-36V-41K	5' LED Lamp, 36VDC, For Canopy/Shelf	4100K	2.2 Lbs.
TL6-36V-30K	6' LED Lamp, 36VDC, For Canopy/Shelf	3000K	2.5 Lbs.
TL6-36V-35K	6' LED Lamp, 36VDC, For Canopy/Shelf	3500K	2.5 Lbs.
TL6-36V-41K	6' LED Lamp, 36VDC, For Canopy/Shelf	4100K	2.5 Lbs.
TL8-36V-30K	8' LED Lamp, 36VDC, For Canopy/Shelf	3000K	3.0 Lbs.
TL8-36V-35K	8' LED Lamp, 36VDC, For Canopy/Shelf	3500K	3.0 Lbs.
TL8-36V-41K	8' LED Lamp, 36VDC, For Canopy/Shelf	4100K	3.0 Lbs.
LED-DRV36V-1L	23W LED Driver, 36V, Single Lamp		2.0 Lbs.
LED-DRV36V-2L	46W LED Driver, 36V, 2 Lamp		2.4 Lbs.